# Proof, Photo & Production media PRODUCT DATASHEET



## EFI Proof Paper 81750BA Matt

### introlled 'ے Onsis

#### **Description:**

The EFI Proof Paper 81750BA Matt was especially developed for proofing of uncoated production papers with high OBA content. It is very suitable for proofing according to FOGRA52.





The mark of ponsible forestry

#### **Application:** Proofing Production

**Technical data:** 175 g/m<sup>2</sup> 230 µm 97 % 5 % [75°] CIE L\*a\*b\* (M0) 96,8 | 2,5 | -7,7 CIE L\*a\*b\* (M1) 97,0 | 3,0 | -10,8 15-30°C (40-60% RH)

#### Size

Weight

Caliper

Opacity

Storage

Gloss

Sheets	Rolls	Core	Rolls	Core
DIN A4 (210 x 297 mm)	25,4 cm x 35 m (10")	3"*)	106,7 cm x 35 m (42")	3"*)
SUPER A4 (241 x 340 mm)	36,0 cm x 35 m (14,17")	3"*)	111,8 cm x 35 m (44")	3"*)
DIN A3 (297 x 420 mm)	43,2 cm x 35 m (17")	3"*)	127,0 cm x 35 m (50")	3"*)
DIN A3+ (330 x 483 mm)	50,8 cm x 35 m (20")	3"*)	152,4 cm x 35 m (60")	3"*)
DIN A2 (420 x 594 mm)	61,0 cm x 35 m (24")	3"*)	162,6 cm x 35 m (64")	3" *)
	91,4 cm x 35 m (36")	3"*)		,

#### \*) supplied with each two adapters 3" to 2" core



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.