



EFI Production Dot Film XF

This universal clear film with a very short drying time provides a basis for films / separations without any chemicals. It produces very sharp plots and possesses a good dot gain control. A Dmax. of 3.2 can be achieved in combination with Ultra Chrome inks, even higher densities with dye based inks.

Description:

Coated clear Film
 Very sharp plots
 Extremely good density with dye-based inks, good with pigmented inks (up to 3.2)
 For dye-based and pigmented inks
 Very even surface

Application:

Layoutfilm
 Dot gain control
 Films for offset and screen printing

Technical data:

Weight	160	g/m ²
Thickness	140	μ
Opacity	/	%
Gloss [Tappi 75°]	/	%
L*a*b* Paper white	/	
Storage	15 - 30 °C (40 - 60% RH)	

Size

Sheet		Roll	Core	Roll	Core	
DIN A4	(210 x 297 mm)	42,0 cm x 15,0 m	(16,5")	2"	106,7 cm x 30,5 m (42")	2"
DIN A3	(297 x 420 mm)	43,2 cm x 30,5 m	(17")	3"*	111,8 cm x 30,5 m (44")	2"
DIN A3+	(330 x 483 mm)	45,7 cm x 30,5 m	(18")	2"	127,0 cm x 30,5 m (50")	2"
DIN A2	(420 x 594 mm)	61,0 cm x 30,5 m	(24")	2"	137,0 cm x 30,5 m (54')	2"
		91,4 cm x 30,5 m	(36")	2"	152,4 cm x 30,5 m (60")	2"

*) supplied with each two adapters 3" to 2" core