



# Proof, Photo & Production media PRODUCT DATASHEET



## EFI Proof Paper 9120XF Matt

Matt coated, tailor-made for contract-proofing applications. For affordable prints with high color fidelity. This proofing paper contains almost zero optical brighteners. The special coloring and the high L-value makes this paper especially suitable for the simulation of matt printing media.



The mark of responsible forestry

### Description:

Matt coated paper  
Wide color gamut  
Easy folding  
Low content of optical brighteners  
Fast drying (Instant-dry)  
Universal use



### Application:

Proofing  
Photo  
Production

### Technical data:

Weight	120	g/m <sup>2</sup>
Thickness	150	μ
Opacity	95	%
Gloss [Tappi 75°]	6	%
L*a*b* Paper white	96,7 / 0,2 / -2,4	
Storage	15 - 30 °C (40 - 60% RH)	

### Sizes

Sheets		Rolls	Core	Rolls	Core
DIN A4	(210 x 297 mm)	25,4 cm x 40 m	(10") 3" *	106,7 cm x 40 m	(42") 3" *
SUPER A4	(241 x 340 mm)	32,9 cm x 10 m	(13") 2"	111,8 cm x 40 m	(44") 3" *
DIN A3	(297 x 420 mm)	36,0 cm x 40 m	(14,17") 3" *	127,0 cm x 40 m	(50") 3" *
DIN A3+	(330 x 483 mm)	43,2 cm x 40 m	(17") 3" *	135,0 cm x 40 m	(53,125") 3" *
A3++	(329 x 558 mm)	50,8 cm x 40 m	(20") 3" *	152,0 cm x 40 m	(60") 3" *
DIN A2	(420 x 594 mm)	61,0 cm x 40 m	(24") 3" *	162,6 cm x 40 m	(64") 3" *
DIN A1	(594 x 841 mm)	91,4 cm x 40 m	(36") 3" *	*) supplied with each two adapters 3" to 2" core	



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.